

FROST Fighter

IDH500QR

Available in Oil/Diesel & LP/NG

Not only is it the most efficient, durable and reliable Indirect Fired Heater available in its class, the IDH500QR is also the one of the quietest at 68dB and offers the most versatile performance features available including standard recirculation for MAXIMUM fuel efficiency savings!



Features:

- Proven & reliable commercial grade burner
- Over 81% efficiency
- Fully Insulated Jacket to minimize heat loss, increase efficiency and provide cool to the touch for safety
- Proven "Multi-Pass" Stainless Steel Heat Exchanger provides unsurpassed heat transfer
- Fully independent fan & combustion air provides consistent and dependable operation in cold weather and ensures pre-heating to eliminate cold air delivery at start-up
- High static pressure/high volume fan provides large volumes of air movement with or without ducting attached
- Available with Dual 12" or Single 16" Outlet that can accommodate up to 100ft. of supply duct
- 16" Intake that can accommodate up to 50ft. of return duct to significantly reduce fuel consumption and heating times (*length of intake duct attached requires equal reduction from 100ft. of supply duct ...e.g: 25ft intake = 75ft supply*)
- Compact design with highly durable 6-Ply Pneumatic tires, handles & lifting bail for easy transport
- Quiet operation of <68dB for noise sensitive areas
- Durable powder coat finish
- High efficiency stainless steel heat exchanger
- Optional fan override switch and power meter display(volts, amps, hertz and watts) available on 'M' models
- **CSA Approved**

Specifications:

Maximum Heating Capacity:	500,000 BTU/h	Standard Fuel Tank Capacity:	42/opt. 60 US Gallons
Fuel Requirement:	Oil/Diesel	Approx. Run Time (Std/Opt):	14/20 hrs
Heated Air Volume:	4,800 CFM	Standard Recirculation:	Yes
Operational Temp. Rating:	-40°C or Colder	Overall Dimensions (LxWxH):	70" x 32" x 57"
Maximum Static Pressure:	3.5"	Approximate Dry Weight:	420lbs
Discharge Temperature:	Up To 250°F (121°C)	Approximate Weight w/ Fuel:	715lbs
Decibel Rating:	68dB	Required Power:	120V/20amp/60Hz

WE. KNOW. HEAT.